



1	A	Backlight (+) +5V
2	K	Backlight (-)
3	VSS	Power ground
4	VDD	Power supply (+5V)
5	VO	Contrast adjust
6	RS	Register select. H:Data; L:Instruction
7	R/W	H: Read; L: Write
8	E	Enable signal
9	DB0	DATA BUS 0
10	DB1	DATA BUS 1
11	DB2	DATA BUS 2
12	DB3	DATA BUS 3
13	DB4	DATA BUS 4
14	DB5	DATA BUS 5
15	DB6	DATA BUS 6
16	DB7	DATA BUS 7

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -10°C~+60°C
5. STORAGE TEMPERATURE: -20°C~+70°C
6. VDD: +5V
7. DRIVE METHOD: 1/16DUTY, 1/5BIAS
8. CONTROLLER: S6A0069 OR EQUIVALENT
9. BACKLIGHT TYPE: YELLOW-GREEN
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

 **WAYING (HONGKONG) SHARES LIMITED**

DESIGN: MODEL NUMBER: **WYM2002A** UNITS: **MM**

CHECK: SHEET: **1 OF 1**

APPROVE:  DATE: 2007-07-12

Unspecified tolerances are ±0.3