



1	/CS
2	/RST
3	A0
4	/WR(R/W)
5	/RD(R)
6	DB0
7	DB1
8	DB2
9	DB3
10	DB4
11	DB5
12	DB6(scl)
13	DB7(scl)
14	VDD
15	VSS
16	V0
17	XV0
18	VG
19	C86
20	P/S
21	VSS

- NOTES:
1. DISPLAY TYPE: STN, YELLOW-GREEN
 2. POLARIZER TYPE: TRANSPARENT, POSITIVE
 3. VIEW DIRECTION: 6:00
 4. OPERATING TEMPERATURE: -20°C~+70°C
 5. STORAGE TEMPERATURE: -30°C~+80°C
 6. VDD: +3.3V
 7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
 8. CONTROLLER: ST7567
 9. BACKLIGHT TYPE: WHITE
 10. BACKLIGHT SUPPLY VOLTAGE: +3.0V



WAYING (HONGKONG) SHARES LIMITED

DESIGN:

MODEL NUMBER:

UNITS: MM

CHECK:

WYM12864K25G

VERSION: A

APPROVE:



SHEET: 1 OF 1

Unspecified tolerances are ±0.3

DATE: 2012-05-19