



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	VO	Contrast adjust
4	/WR	Data write
5	/RD	Data read
6	/CS	Chip select for RA8835A.
7	A0	H: Command; L:Data
8	/RST	Reset signal
9-16	D0-D7	DATA BUS
17	NC	No connection
18	VEE	Negative power output
19	A	Backlight power supply(+5V)
20	K	Backlight power supply(-)

NOTES:

1. DISPLAY TYPE: STN, BLUE
2. POLARIZER TYPE: TRANSMISSIVE, NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/240DUTY,1/17BIAS
8. CONTROLLER: RA8835A
9. BACKLIGHT TYPE: WHITE,LED
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM320240B-SBTSESWD	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3			DATE:	2006-05-25	