



真值表:



1	VDD	Power supply (+3.3V)
2	VSS	Power ground
3	/CS	Chip Select ("1" active)
4	A0	H: Command; L:Data
5	/RD	Data read
6	/WR	Data write
7	/RST	Reset signal
8	DB0	Data Bus DB0
9	DB1	Data Bus DB1
10	DB2	Data Bus DB2
11	DB3	Data Bus DB3
12	DB4	Data Bus DB4
13	DB5	Data Bus DB5
14	DB6	Data Bus DB6
15	DB7	Data Bus DB7
16	NC	No connection
17	A	Backlight (+) +3.3V
18	K	Backlight (-)
19	NC	No connection
20	NC	No connection

NOTES:

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/128DUTY,1/12BIAS
8. CONTROLLER: UC1698
9. BACKLIGHT TYPE: WHITE,SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

DESIGN:	MODEL NUMBER:
CHECK:	WYM240128K1
APPROVE:	UNITS: MM
Unspecified tolerances are ±0.3	VERSION: A
	SHEET: 1 OF 1
	DATE: 2008-07-20